



DIMENSIONS IN INCHES

DIMENSIONAL DATA

| DIM. | MIN.  | MAX.  | REF. |
|------|-------|-------|------|
| A    | 2.336 | 2.450 |      |
| B    | 2.028 | 2.088 |      |
| C    | 1.005 | 1.000 |      |
| D    | 6.75  | 7.00  |      |
| E    | .305  | .370  |      |
| F    | .305  | .370  |      |
| G    | .950  | .985  |      |
| H    | .360  | .387  |      |
| J    | 5.40  | 5.75  |      |
| K    | .220  | .275  |      |
| L    | .311  | .375  |      |
| M    | .031  | .062  | .188 |
| P    | .030  | .096  |      |

- NOTES
1. SOCKET SPECIFICATIONS
  2. MATH. & FINISHES
  3. SOCKET BODY - 96% ALUMINUM CER.
  4. CONTACTS - NON-FERROUS SPRING ALLOY, HEAT TREATED & AG. P.
  5. WT. .093 LB. MAX.
  6. OPER. TEMP. - 175°C MAX.
  7. DIMS. ARE FOR INFO ONLY & ARE NOT REPRODUCIBLE FOR PRODUCTION PURPOSES.

|     |  |      |         |     |      |    |
|-----|--|------|---------|-----|------|----|
| NO. | DESCRIPTION OF CHANGE                      | REQ. | DATE    | BY  | DATE | BY |
|     | DRAWN                                      |      | 2-1-67  |     |      |    |
| 1   | CHANGED DIMS & DROPPED MIN. MAX. DIM. 0    |      | 2-24-67 | CDK |      |    |
| 2   | FIXED MIN. 2.208 MAX. N 2.336 I. 5.700 K 7 |      |         |     |      |    |

DRAWN: ELS  
 CHECKED: 2-1-67  
 SCALE: NONE  
 DIVISION: PAT. & SUPPLIES  
 NO. SK-660A-60  
 SHEET: 2  
 TOTAL SHEETS: 2

MITTEL-MCCULLOUGH INC.  
 SAN CARLOS, CALIF.  
 SK-660A  
 SOCKET - ELECTRON TUBE  
 SK-660A-60